

**Datasheet**  
Elegance coffin trolley  
Product code 1081

Rev. 0 of 31/10/2024



1/5

# Datasheet

Elegance coffin trolley

Product code 1081

Rev. 0 of 31/10/2024



## DESCRIPTION

### Structure

- Elegance coffin trolley made of Ø mm galvanized steel round tube. 30x1.5 shaped and rectangular galvanized steel tube mm. 40x20x1.5; the structure is made integral by crosspieces in galvanized steel profiles. On the two opposite sides, decorative circles in Ø mm galvanized steel round tube. 20x1.5; each circle is characterized, on the inside, by Christian crosses made of solid galvanized round Ø mm. 12.
- N. 3 puncture-proof elastic rubber wheels of Ø mm. 400 approx. with steel rim (of which 1 swivel with brake).
- Removable sedan chair made of 15/10 thick galvanized steel sheet and mm. rectangular galvanized steel tube. 40x20x1.5.
- N. 4 handles for gripping, towed lifting of the trolley in Ø mm galvanized steel round tube. 32x1.5; In order to allow a secure grip, the handles are equipped with PVC knobs. N. 4 galvanized solid round hooks and n. 2 nylon straps complete with buckles for securing the coffin.

### Dimensions

- Total height cm. 75;
- Total width cm. 80;
- Total length cm. 240;
- Support surface length cm. 160;
- Maximum capacity allowed kg. 200;
- Weight kg. 73.

---

COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 7038  
( Steel parts )

Customers can request a different finish from the RAL color options available on our website.

---

PRODUCT VARIANTS



[Product code 1080 - Coffin trolley](#)

# Datasheet

Elegance coffin trolley

Product code 1081

Rev. 0 of 31/10/2024



---

## ANTICORROSIVE TREATMENTS AND FINISHES

### Washing

Spray treatment for removing oil and grease from metal surfaces using special degreasing liquids. Subsequent drying in dryer for 15 minutes.

### Sandblasting

Manual sandblasting process with river sand, which increases the porosity of metal surfaces and thus the adhesion of thermosetting powders.

### Anti-corrosive application

First painting cycle with an anticorrosive thermosetting powder primer based on epoxy resins and special pigments. It provides adequate protection against weathering.

### Anticorrosive polymerization

Baking in an industrial curing oven at a temperature of 180°C. During this stage, the powder turns into a uniform, smooth and durable coating.

### Colored finish application

Final coating cycle with thermosetting powders. Application follows the same principles as the anticorrosive.

### Polymerization colored finish

Final baking in an industrial curing oven at a temperature of 180°C. The procedure follows the same principles as the curing of the anticorrosive. The powder is transformed into a uniform coating, and the surface appearance takes on the characteristics of the chosen color type, e.g. smooth, textured, wrinkled, etc.

---

**DELIVERY**

Product supplied already assembled, no need for fastening hardware.

---

**FIXING**

---

**CORPORATE CERTIFICATIONS**

**ISO 9001:2015**

Quality management system.

**UNI EN ISO 3834-3:2021**

Welding quality management system.

**Processing center**

Certificate of Processing Center