




1/5



Dimcar reserves the right to make, at any time, changes on the products deemed useful to improve the quality of the same; the images contained in the sheets may not faithfully reproduce the real colors of the items.

DESCRIPTION

Structure

Square Totem composed of N. 4 support uprights in round tube of galvanized steel Ø mm. 60x2 (lower part) and Ø mm. 46x2 (upper part) with intermediate decorative reduction element; flange at the base for fixing to the ground.

- N. 4 noticeboards in boxed galvanized steel thickness mm. 1.2; upper door that can be opened in galvanized steel profiles with triangular key lock.
- Reading side in compact transparent unbreakable polycarbonate, protected from UV rays and particularly suitable for outdoor use thickness mm. 3.
- Plates (removable) in the upper part, to affix the possible name of the Municipality; affixing by means of magnets.
- Cover with base frame in galvanized profile thickness mm. 1.5 shaped cantilevered; pyramid made of galvanized sheet metal thickness mm. 1.2 with decorative friezes.

Total weight: 156Kg

COLOR FINISH AS PROVIDED IN THE CATALOG



Gunmetal gray
(Steel parts)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT OPTIONALS

Product code 185-AD -

PRODUCT VARIANTS



Product code 187 - Triangular Totem

ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment for removing oil and grease from metal surfaces using special degreasing liquids. Subsequent drying in dryer for 15 minutes.

Sandblasting

Manual sandblasting process with river sand, which increases the porosity of metal surfaces and thus the adhesion of thermosetting powders.

Anti-corrosive application

First painting cycle with an anticorrosive thermosetting powder primer based on epoxy resins and special pigments. It provides adequate protection against weathering.

Anticorrosive polymerization

Baking in an industrial curing oven at a temperature of 180°C. During this stage, the powder turns into a uniform, smooth and durable coating.

Colored finish application

Final coating cycle with thermosetting powders. Application follows the same principles as the anticorrosive.

Polymerization colored finish

Final baking in an industrial curing oven at a temperature of 180°C. The procedure follows the same principles as the curing of the anticorrosive. The powder is transformed into a uniform coating, and the surface appearance takes on the characteristics of the chosen color type, e.g. smooth, textured, wrinkled, etc.

DELIVERY

Product supplied in assembly kit with steel hardware and instructions for mounting and grounding.

FIXING

The product must be installed by cementing.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality management system.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate of Processing Center