




1/5



Dimcar reserves the right to make, at any time, changes on the products deemed useful to improve the quality of the same; the images contained in the sheets may not faithfully reproduce the real colors of the items.

Datasheet

Large Trash Bin Mida

Product code 228

Rev. 0 of 10/07/2017



DESCRIPTION

Structure

The Mida bin is characterized by its cylindrical shape, and flared at the top; it is made with 21 shaped profiles in galvanized flat iron measuring 30x3 mm, connected in the lower, central and upper part by 3 connecting rings.

- Upper part edged with a ring in galvanized round tube measuring \varnothing 20x1.5 mm.
- Base made of galvanized steel profiles.
- Internal container (removable) in galvanized sheet metal, equipped with a handle.

Overall weight: 25Kg

Datasheet

Large Trash Bin Mida

Product code 228

Rev. 0 of 10/07/2017



COLOR FINISH AS PROVIDED IN THE CATALOG



Gunmetal gray
(Steel parts)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT VARIANTS



[Product code 228-BIS - Large Trash Bin Mida with Lid and ashtray](#)

Datasheet

Large Trash Bin Mida

Product code 228

Rev. 0 of 10/07/2017



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment for removing oil and grease from metal surfaces using special degreasing liquids. Subsequent drying in dryer for 15 minutes.

Sandblasting

Manual sandblasting process with river sand, which increases the porosity of metal surfaces and thus the adhesion of thermosetting powders.

Anti-corrosive application

First painting cycle with an anticorrosive thermosetting powder primer based on epoxy resins and special pigments. It provides adequate protection against weathering.

Anticorrosive polymerization

Baking in an industrial curing oven at a temperature of 180°C. During this stage, the powder turns into a uniform, smooth and durable coating.

Colored finish application

Final coating cycle with thermosetting powders. Application follows the same principles as the anticorrosive.

Polymerization colored finish

Final baking in an industrial curing oven at a temperature of 180°C. The procedure follows the same principles as the curing of the anticorrosive. The powder is transformed into a uniform coating, and the surface appearance takes on the characteristics of the chosen color type, e.g. smooth, textured, wrinkled, etc.

Datasheet

Large Trash Bin Mida

Product code 228

Rev. 0 of 10/07/2017



DELIVERY

Product supplied in assembly kit with steel hardware and instructions for mounting and grounding.

FIXING

The product is prepared for fixing to the ground using anchor bolts and expansion plugs.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality management system.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate of Processing Center