




1/5



Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

---

## DESCRIPTION

### Structure

Ashtray Fumino consisting of a support upright made by shaping a 150x8 mm galvanized plate; equipped with a vertical stiffening support in 60x6 mm galvanized flat iron. The upright is equipped with holes in the lower part for fixing to the ground. Upper part of the upright characterized by stylised slots for the introduction of cigarette butts; the first slot contains a micro-perforated sheet metal inside intended for extinguishing the cigarette; the second slot gives access to the internal container.

- Ashtray consisting of a container in galvanized sheet metal thickness mm. 1.2 with rounded lower edge and equipped with a single key lock.

**Overall weight:** 13Kg

# Datasheet

Ashtray Fumino

Product code 367

Rev. 0 of 10/06/2016



---

## COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 3002  
( Basket )



RAL 9010  
( Support )

Customers can request a different finish from the RAL color options available on our website.

---

## ANTICORROSIVE TREATMENTS AND FINISHES

### Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

### Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

### Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

### Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

### Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

### Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

---

## DELIVERY

The product comes with an assembly kit that includes steel screws and instructions for mounting and fixing.

---

## FIXING

The product is designed to be fixed to the ground using expansion anchors and dowels.

---

## CORPORATE CERTIFICATIONS

### ISO 9001:2015

Quality Management System.

### UNI EN ISO 3834-3:2021

Welding quality management system.

### Processing center

Certificate according to Italian Law D.M. of 14 Jan 2008