

Datasheet


Cenerino ashtray wall mounting

Product code 408-M

Rev. 0 of 10/06/2016



1/5



Dimcar reserves the right to make, at any time, changes on the products deemed useful to improve the quality of the same; the images contained in the sheets may not faithfully reproduce the real colors of the items.

Datasheet

Cenerino ashtray wall mounting

Product code 408-M

Rev. 0 of 10/06/2016



DESCRIPTION

Structure

Ashtray Cenerino with wall attachment composed of a rear box made of galvanized sheet metal thickness mm. 1.2 with provision for wall fixing. Shaped container made of galvanized sheet metal thickness mm. 1.5 with rounded edges on the front; complete with micro-perforated plate for extinguishing cigarettes, made of polished AISI 304 stainless steel sheet thickness mm.

- Bottom in galvanized steel sheet with holes for draining rainwater.

Overall weight: 2Kg

Datasheet

Cenerino ashtray wall mounting

Product code 408-M

Rev. 0 of 10/06/2016



COLOR FINISH AS PROVIDED IN THE CATALOG



Rust
(Steel parts)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT VARIANTS



Product code 408-BIS - Ashtray Cenerino with bollard



Product code 408 - Ashtray Cenerino mounting on existing pole

Datasheet

Cenerino ashtray wall mounting

Product code 408-M

Rev. 0 of 10/06/2016



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment for removing oil and grease from metal surfaces using special degreasing liquids. Subsequent drying in dryer for 15 minutes.

Sandblasting

Manual sandblasting process with river sand, which increases the porosity of metal surfaces and thus the adhesion of thermosetting powders.

Anti-corrosive application

First painting cycle with an anticorrosive thermosetting powder primer based on epoxy resins and special pigments. It provides adequate protection against weathering.

Anticorrosive polymerization

Baking in an industrial curing oven at a temperature of 180°C. During this stage, the powder turns into a uniform, smooth and durable coating.

Colored finish application

Final coating cycle with thermosetting powders. Application follows the same principles as the anticorrosive.

Polymerization colored finish

Final baking in an industrial curing oven at a temperature of 180°C. The procedure follows the same principles as the curing of the anticorrosive. The powder is transformed into a uniform coating, and the surface appearance takes on the characteristics of the chosen color type, e.g. smooth, textured, wrinkled, etc.

4/5

Dimcar reserves the right to make, at any time, changes on the products deemed useful to improve the quality of the same; the images contained in the sheets may not faithfully reproduce the real colors of the items.

Datasheet

Cenerino ashtray wall mounting

Product code 408-M

Rev. 0 of 10/06/2016



DELIVERY

Product supplied already assembled with steel hardware and instructions for ground fixing.

FIXING

The product is prepared for wall mounting using anchor bolts and expansion plugs.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality management system.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate of Processing Center