

Datasheet


Giglio seat of cm. 130

Product code 417

Rev. 1 of 23/06/2017



1/5



Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Giglio seat of cm. 130

Product code 417

Rev. 1 of 23/06/2017



DESCRIPTION

Structure

Giglio Bench composed of N. 2 supports made of rectangular tube of galvanized steel mm. 60x40x2. Each single support is equipped inside with a decorative shape in galvanized sheet metal thickness mm. 3 characterized by decorative stylised floral carvings.

- The supports are equipped at the base with holes for fixing to the ground.
- Seat made of a single box in galvanized sheet steel thickness mm. 3 characterized by decorative rhomboidal and oblong inclined holes.

Overall weight: 28Kg

Datasheet

Giglio seat of cm. 130

Product code 417

Rev. 1 of 23/06/2017




COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 1013b
(Seating)



RAL 1013
(Seating)



RAL 3005
(Supports)

Customers can request a different finish from the RAL color options available on our website.

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Giglio seat of cm. 130

Product code 417

Rev. 1 of 23/06/2017



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Giglio seat of cm. 130

Product code 417

Rev. 1 of 23/06/2017



DELIVERY

The product comes with an assembly kit that includes steel screws and instructions for mounting and fixing.

FIXING

The product is designed to be fixed to the ground using expansion anchors and dowels.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 14 Jan 2008