



1/5



DESCRIPTION

Structure

Color and creativity come together to create a one-of-a-kind seat, the Fumettors seat, designed for use by children. Bright colors, all child-friendly. Made of boxes made of 2 mm thick galvanized steel sheet, appropriately shaped. The structure is equipped with a frame at the base for possible fixing to the ground. Single side equipped with a graphic sticker recalling the classic exclamations "SUPER! - BOING - GULP!". The basic finish for the metal parts of this product is made up of the following colors, specifically:

color "matt traffic red RAL 3020" for the wording SUPER!

color "matt zinc yellow RAL 1018" for the wording BOING

color "matt sky blue RAL 5012" for the wording GULP!

The customer can however request a different finish, choosing from the RAL colors available on our website. The painting technique adopted for the galvanized steel structure is with thermosetting powders with oven baking.

Overall weight: 29Kg

Datasheet

Fumettors

Product code D874

Rev. 0 of 05/09/2024



COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 3020
(Steel parts)

Customers can request a different finish from the RAL color options available on our website.

Datasheet

Fumettors

Product code D874

Rev. 0 of 05/09/2024



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5

DELIVERY

The product comes with steel screws and fixing instructions.

FIXING

The product is designed to be fixed to the ground using expansion anchors and dowels.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 14 Jan 2008