

Datasheet


PopUp large trash bin

Product code G538

Rev. 0 of 05/09/2024



1/5



DESCRIPTION

Structure

Shaped external support, characterized by a decorative "comma" positioned at the base (front and rear side), made of 5 mm thick galvanized sheet metal. Rear paneling in 1.5 mm thick galvanized sheet metal and front door, made of 1.5 mm thick galvanized steel profiles, with posting space, equipped with an opening for emptying operations. Waste is introduced through the upper hole with delivery to a special internal container made of galvanized sheet metal. Display panel made of 3 mm thick transparent compact polycarbonate.

Overall weight: 103Kg

Datasheet

PopUp large trash bin

Product code G538

Rev. 0 of 05/09/2024



COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 1018
(Support)



RAL 7016
(External panel and door)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT OPTIONALS



Product code 431 - Ashtray Bond

Datasheet

PopUp large trash bin

Product code G538

Rev. 0 of 05/09/2024



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5



DELIVERY

The product comes with an assembly kit that includes steel screws and instructions for mounting and fixing.

FIXING

The product is designed to be fixed to the ground using expansion anchors and dowels.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 14 Jan 2008