


Datasheet


Baby snake seat

Product code D833

Rev. 0 of 10/03/2022



1/5



Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Baby snake seat

Product code D833

Rev. 0 of 10/03/2022



DESCRIPTION

Structure

What distinguishes the Baby Snake bench is the sinuous shape, characteristic of the snake; The entire structure is made of square-section galvanized steel tubes and consists of 2 interconnected monoblocks, each including two feet; each single foot is equipped with a base plate in galvanized sheet metal with a hole for fixing to the ground. All the edges of the structure are free of sharp edges.

The openings do not cause the risk of fingers being trapped.

Overall weight: 52Kg

Datasheet

Baby snake seat

Product code D833

Rev. 0 of 10/03/2022



COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 1018
(Steel parts)



RAL 2000
(Steel parts)

Customers can request a different finish from the RAL color options available on our website.

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Baby snake seat

Product code D833

Rev. 0 of 10/03/2022



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Baby snake seat

Product code D833

Rev. 0 of 10/03/2022



DELIVERY

The product comes with steel screws and fixing instructions.

FIXING

The product is designed to be fixed to the ground using expansion anchors and dowels.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018