


Datasheet

Bon large trash bin
Product code G514

Rev. 0 of 08/02/2023



2/5

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Bon large trash bin
Product code G514

Rev. 0 of 08/02/2023



DESCRIPTION

Structure

With a particular cylindrical shape, consisting of an internal shaft made of 2 mm thick galvanized sheet metal and equipped with holes at the base for the drainage of rainwater. Circular upper ring made of 3 mm thick galvanized sheet metal obtained by laser cutting, complete with circular hole for the introduction of waste.

- External panels with a particular shape, made of 2 mm thick galvanized sheet metal, and characterized by an oblique notch that extends along the entire bin.

Overall weight: 44Kg

Datasheet

Bon large trash bin
Product code G514


Rev. 0 of 08/02/2023



FINISH ACCORDING TO THE CATALOGUE



RAL 9010
(Panels)



RAL 7005
(Inner stem)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT VARIANTS



Product code G514-BIS - Bob outdoor waste bin with lid



Product code G515 - Bob large trash bin with ashtray



Product code G515-BIS - Bob large trash bin with lid and ashtray

Datasheet

Bon large trash bin
Product code G514

Rev. 0 of 08/02/2023



TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

2/5

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Bon large trash bin
Product code G514

Rev. 0 of 08/02/2023



DELIVERY

Prodotto fornito in kit di assemblaggio con viteria in acciaio ed istruzioni per il montaggio e fissaggio.

FIXING

Il prodotto è predisposto per il fissaggio al suolo mediante tirafondi e tasselli ad espansione.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018