




DESCRIPTION


Structure

The Giglio Basket is made up of a support upright in 60x60x1.5 mm galvanized steel square tube with a shaped galvanized steel cap at the top. Shaped lid, obtained from high definition plasma cutting, complete with a 4 mm thick galvanized steel sheet reinforcement bezel; shaped lower support in 25x25x1.5 mm galvanized steel square tube.

- Square-shaped basket with 4 rounded corners in 1.5 mm thick galvanized sheet metal; on three sides, the basket is characterized by stylised decorative floral carvings; bag-holding ring made of 3 mm thick galvanized sheet metal; bottom in galvanized sheet metal with holes for draining rainwater.

Overall weight: 18Kg

FINISH ACCORDING TO THE CATALOGUE



RAL 3005
(Support upright, lid and bag-holding ring)



RAL 1013
(Basket)



RAL 1015
(Basket)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT OPTIONALS



Product code 431 - Ashtray Bond

TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

DELIVERY

Prodotto fornito in kit di assemblaggio con viteria in acciaio ed istruzioni per il montaggio e fissaggio.

FIXING

Il prodotto deve essere installato mediante cementazione.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018