



Datasheet

Gommina the seat
Product code D870

Rev. 0 of 07/02/2023



1/5



Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Gommina the seat
Product code D870

Rev. 0 of 07/02/2023



DESCRIPTION

Structure

Color and creativity come together to create a one-of-a-kind seat, the Gommina bench was born as a new form of furniture designed for use by children. Bright colors, all child-friendly. The Gommina bench is made of boxes made of 2 mm thick galvanized steel sheet, shaped and obtained by cutting with laser technology. The supports are subsequently assembled to form a single block with the characteristic "rubber" shape. The appearance is most distinguished by the central horizontal band, made of galvanized and shaped sheet metal.

The Gommina bench is equipped with a frame at the base for possible fixing to the ground.

Overall weight: 37Kg

Datasheet

Gommina the seat
Product code D870


Rev. 0 of 07/02/2023



COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 5017
(Boxed)



RAL 3003
(Boxed)



RAL 9016
(Central band)

Customers can request a different finish from the RAL color options available on our website.

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Gommina the seat
Product code D870

Rev. 0 of 07/02/2023



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

DELIVERY

The product comes with steel screws and fixing instructions.

FIXING

The product is designed to be fixed to the ground using expansion anchors and dowels.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018