




Datasheet

Large trash bin Heron

Product code 359

Rev. 0 of 10/06/2016



DESCRIPTION

Structure

The Heron waste bin is characterised by its ellipsoidal shape; made of 2 mm thick galvanised sheet metal, with circular holes on the two opposing ends. Characterised by N. 2 Nordic pine wood bands set into the sides of the structure. Opening upper part, made of 4 mm thick galvanised sheet metal with an ellipsoidal hole (central) for inserting waste; opening and closing is ensured by a lock.

- Inside the waste bin is equipped with N. 1 bag holder shaped in galvanised solid round and foldable.
- Base in galvanised sheet metal with holes for draining rainwater.

Overall weight: 30Kg

Datasheet

Large trash bin Heron

Product code 359

Rev. 0 of 10/06/2016



FINISH ACCORDING TO THE CATALOGUE



Brilliant aluminum
(Steel parts)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT OPTIONALS



Product code 431 - Ashtray Bond

Datasheet

Large trash bin Heron

Product code 359

Rev. 0 of 10/06/2016



TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

2/5

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Large trash bin Heron

Product code 359

Rev. 0 of 10/06/2016



DELIVERY

Prodotto fornito in kit di assemblaggio con viteria in acciaio ed istruzioni per il montaggio e fissaggio.

FIXING

Il prodotto è predisposto per il fissaggio al suolo mediante tirafondi e tasselli ad espansione.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018