




DESCRIPTION

Structure

Liberty ashtray consisting of a sinuous support upright, made of galvanized steel round tube Ø mm. 76x2 (lower part) and galvanized steel round tube Ø mm. 60x2 (upper part) with a decorative intermediate element in turned steel. The upright is adorned in the upper part with a frieze and equipped with a circular plate at the base in galvanized sheet metal thickness mm. 4. The plate is equipped with holes for fixing to the ground. Shaped ashtray container, circular in shape, made of galvanized sheet metal thickness mm. 3 complete with a micro-perforated plate for extinguishing cigarettes.

- The semi-circular plate is made of polished AISI 304 stainless steel sheet thickness mm. 1. Front support arch, with decorative function, made of galvanized rectangular tube mm. 50x20x3.

Overall weight: 13Kg

FINISH ACCORDING TO THE CATALOGUE



Gun metal gray
(Steel parts)

Customers can request a different finish from the RAL color options available on our website.

TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

5/5

DELIVERY

Prodotto fornito in kit di assemblaggio con viteria in acciaio ed istruzioni per il montaggio e fissaggio.

FIXING

Il prodotto è predisposto per il fissaggio al suolo mediante tirafondi e tasselli ad espansione.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018