


Datasheet

Bin Mida with lid
Product code 312-BIS

Rev. 0 of 10/06/2016



Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Bin Mida with lid

Product code 312-BIS

Rev. 0 of 10/06/2016



DESCRIPTION

Structure

The Mida basket with lid is made up of a support upright in round galvanized steel tube Ø mm. 76x2 adorned in the upper part with a decorative frieze; shaped lid in galvanized sheet metal mm. 3 with reinforcement bezel, in galvanized steel sheet obtained from high definition plasma cutting. Shaped lower support for supporting the basket in galvanized steel sheet obtained from plasma cutting and characterized by decorative carvings.

- Cylindrical basket, with flaring in the upper part, made with N. 20 shaped galvanized iron strips Ø mm. 30x3; upper part edged with a ring in galvanized round tube Ø mm. 20x5; shaped bottom in galvanized sheet metal thickness mm. 1.5 with holes for draining rainwater.

Overall weight: 15Kg

Datasheet

Bin Mida with lid

Product code 312-BIS

Rev. 0 of 10/06/2016



FINISH ACCORDING TO THE CATALOGUE



Gun metal gray
(Steel parts)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT OPTIONALS



Product code 431 - Ashtray Bond

PRODUCT VARIANTS



Product code 312-BIS-T - Triple Mida litter bin with lid and ashtray



Product code 312 - Bin Mida

Datasheet

Bin Mida with lid

Product code 312-BIS

Rev. 0 of 10/06/2016



TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

1/5

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

DELIVERY

Prodotto fornito in kit di assemblaggio con viteria in acciaio ed istruzioni per il montaggio e fissaggio.

FIXING

Il prodotto deve essere installato mediante cementazione.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018