




Datasheet

Flower box Ozan

Product code 439

Rev. 2 of 04/08/2023



DESCRIPTION

Structure

Ozan planter composed of an upper ring made of a rectangular tube of galvanized steel measuring 50x20x2 mm. Trunk of truncated conical shape, made of a panel of galvanized steel sheet thickness 1.5 mm. No. 3 feet with staggered profile welded to the base and arranged at 120° between them. Internal container made of galvanized sheet metal.

Overall weight: 40Kg

Datasheet

Flower box Ozan

Product code 439

Rev. 2 of 04/08/2023



FINISH ACCORDING TO THE CATALOGUE



Gun metal gray
(External shell)



RAL 7001
(Inner tank)

Customers can request a different finish from the RAL color options available on our website.

TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

5/5

DELIVERY

Prodotto fornito già assemblato con viteria in acciaio ed istruzioni per il fissaggio.

FIXING

Il prodotto non necessita di ancoraggio al suolo.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018