

Datasheet


Portland seat with backrest

Product code G545

Rev. 0 of 13/02/2019



1/5



Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Portland seat with backrest

Product code G545

Rev. 0 of 13/02/2019



DESCRIPTION

Structure

With its modern and essential shapes, the Portland seat is characterized by a modular system of individual seats. Base support and shaped armrest, made of 60x6 mm flat iron; the supports are equipped with support feet at the base.

- Anatomically shaped seat shells, made of 2 mm galvanized steel sheet, obtained by high definition plasma cutting.
- The panels are characterized by decorative slits on the backrest and seat.
- Crosspiece connecting shells/supports made of Ø 80x2 galvanized steel round tube.

Overall weight: 77Kg

Datasheet

Portland seat with backrest

Product code G545

Rev. 0 of 13/02/2019



COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 5015
(Seating shells)



RAL 7016
(Armrest and crossbar support)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT VARIANTS



Product code G546 - Portland seat without backrest

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Portland seat with backrest

Product code G545

Rev. 0 of 13/02/2019



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Portland seat with backrest

Product code G545

Rev. 0 of 13/02/2019



DELIVERY

The product comes with an assembly kit that includes steel screws and instructions for mounting and fixing.

FIXING

The product does not require anchoring to the ground.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 14 Jan 2008