

Target iron litter bin
Product code 607-CO-M

 City
Life
Design
DIMCAR

dimcar.it



P.I. C.F. 031129830752
REA LE 200574 CAP SOC. SOC. € 2.000.000.00

DESCRIPTION




Structure

"Target" from the English literally "objective", a bin characterized by its structure that visually declared on the outside draws a target, a silent invitation not to disperse waste and collect it inside. Different types of covering offer the possibility of adapting the final appearance to the surrounding area. The result is a universal bin, with a linear shape, usable in public spaces outdoors but also indoors. For smokers it is available with a built-in ashtray, protected from rainwater that could otherwise disperse its contents.

- Main frame made of laser-cut shaped supports, made of 6 mm thick sheet metal; external paneling shaped and made of 1.5 mm thick galvanized sheet metal.
- The bin is equipped with holes for the introduction of waste on all four sides.
- Opening of the bin with a door with an appropriate lock and internal container with a capacity of approximately 40 litres, made of galvanized sheet metal and equipped with handles for extracting and removing the bag (not supplied).
- An upper corner of the bin features an ashtray (removable) with holes for extinguishing and inserting cigarette butts.
- Lower plinth made of galvanized sheet metal and equipped with holes for fixing to the ground.

Overall weight: 41Kg

COLOR FINISH AS PROVIDED IN THE CATALOG



Customers can request a different finish from the RAL color options available on our website.

PRODUCT VARIANTS



[Product code 607-CO-L - Targhet wood litter bin](#)

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

Datasheet

Target iron litter bin
Product code 607-CO-M

Rev. 0 of 04/07/2024



ANTICORROSIVE TREATMENTS AND FINISHES

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles



DELIVERY

The product comes with steel screws and fixing instructions.

FIXING

The product is designed to be fixed to the ground using expansion anchors and dowels.

CORPORATE CERTIFICATIONS

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 14 Jan 2008

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles