




Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Bin Trio with ashtray

Product code 376

Rev. 0 of 20/12/2016



DESCRIPTION

Structure

The Trio wastebasket with ashtray is made up of a support upright in round tubular galvanized steel Ø mm. 80x2, with a decorative flange at the base to cover the hole made for burial. Upper ashtray, circular in shape, equipped with a micro-perforated plate for extinguishing cigarettes; the plate is semi-circular in shape and is made of polished AISI 304 stainless steel sheet, thickness mm. 1; the extraction of the ashtray is guaranteed by a lock.

- No. 3 shaped folding lids, made of galvanized sheet metal, thickness mm. 3; the folding of the lids facilitates the extraction of any internal bags.
- No. 3 shaped lower arms, to support the basket, with a decorative element in galvanized flat iron.
- No. 3 cylindrical baskets, made of galvanized sheet metal, thickness mm. 1 with alternating circular holes of Ø mm. 6, upper part with anti-cut edges and labels indicating the type of collection; bottom made of 1 mm thick galvanized steel sheet, with holes for draining rainwater.

Overall weight: 26Kg

Datasheet

Bin Trio with ashtray

Product code 376

Rev. 0 of 20/12/2016



FINISH ACCORDING TO THE CATALOGUE



RAL 9016
(Basket and lid)



Gun metal gray
(Upright)



RAL 1018
(Basket and lid)



RAL 5017
(Basket and lid)

Customers can request a different finish from the RAL color options available on our website.

Datasheet

Bin Trio with ashtray

Product code 376

Rev. 0 of 20/12/2016



TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Bin Trio with ashtray

Product code 376

Rev. 0 of 20/12/2016



DELIVERY

Prodotto fornito in kit di assemblaggio con viteria in acciaio ed istruzioni per il montaggio e fissaggio.

FIXING

Il prodotto deve essere installato mediante cementazione.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018