

# Datasheet


Tubetto seat with flower box

Product code G556

Rev. 0 of 07/08/2020



1/5



Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

# Datasheet

Tubetto seat with flower box

Product code G556

Rev. 0 of 07/08/2020



## DESCRIPTION

### Structure

The Tubetto seat with flowerpot is made up of a cylindrical main stem (flowerpot), made of 3 mm thick galvanized steel sheet, featuring decorative carvings obtained by laser cutting, depicting a "smiling face". Inside the stem is equipped with a galvanized steel tray for the insertion of plants. No. 2 seats at the base, semi-circular in shape, made of 2 mm thick galvanized steel, equipped with a galvanized sheet metal seat with a rounded profile.

**Overall weight:** 61Kg

# Datasheet


Tubetto seat with flower box

Product code G556

Rev. 0 of 07/08/2020



## COLOR FINISH AS PROVIDED IN THE CATALOG



RAL 7005  
( Inner tank and seat shell )



RAL 1018  
( Basket and seat )

Customers can request a different finish from the RAL color options available on our website.

# Datasheet

Tubetto seat with flower box

Product code G556

Rev. 0 of 07/08/2020



## ANTICORROSIVE TREATMENTS AND FINISHES

### Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

### Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

### Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

### Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

### Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

### Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

4/5

Dimcar has the authority to make changes to the products that are useful for improving their quality. The images on the cards may not accurately portray the actual colors of the articles

# Datasheet

Tubetto seat with flower box

Product code G556

Rev. 0 of 07/08/2020



---

## DELIVERY

The product comes with steel screws and fixing instructions.

---

## FIXING

The product is designed to be fixed to the ground using expansion anchors and dowels.

---

## CORPORATE CERTIFICATIONS

### ISO 9001:2015

Quality Management System.

### UNI EN ISO 3834-3:2021

Welding quality management system.

### Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018