


Datasheet

Flower Box Versilia with circular bench

Product code 244-BIS

Rev. 1 of 04/08/2023



1/5

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Flower Box Versilia with circular bench

Product code 244-BIS

Rev. 1 of 04/08/2023



DESCRIPTION

Structure

Versilia planter with bench, circular in shape composed of a double base ring in rectangular tube of galvanized steel mm. 50x30x2. The base is equipped with N. 3 feet that prevent direct contact of the structure with the ground. N. 8 rings in rectangular tube of galvanized steel mm. 50x30x2. Internal container made of galvanized sheet metal. Circular seat made of N. 8 rings in round tube of galvanized steel mm. 20x1.5 and an external ring in oval section galvanized steel tube mm. 40x20x1.5. The rings are welded on special supports in galvanized steel.

Overall weight: 127

Datasheet

Flower Box Versilia with circular bench

Product code 244-BIS

Rev. 1 of 04/08/2023



FINISH ACCORDING TO THE CATALOGUE



RAL 7038
(External shell)



Gun metal gray
(Inner tank)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT VARIANTS



[Product code 244 - Flower Box Versilia](#)

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Flower Box Versilia with circular bench

Product code 244-BIS

Rev. 1 of 04/08/2023



TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

1/5

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Flower Box Versilia with circular bench

Product code 244-BIS

Rev. 1 of 04/08/2023



DELIVERY

Prodotto fornito in kit di assemblaggio con viteria in acciaio ed istruzioni per il montaggio e fissaggio.

FIXING

Il prodotto non necessita di ancoraggio al suolo.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018