


Datasheet

Large trash bin Ziggy

Product code G473

Rev. 0 of 01/06/2018



Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

DESCRIPTION

Structure

With a particular ellipsoidal shape, consisting of a rear panel and front door made of 1.5 mm thick galvanized sheet metal; the door (with book-like opening) is equipped with an internal bag-holding ring and a single key lock.

- Cylindrical barrel made of 2 mm thick galvanized steel profiles; the structure is characterized on the sides by two shaped bands in 2 mm thick galvanized sheet metal; inside the bin is equipped with plates for fixing to the ground.
- Shaped upper ring, with hole for inserting waste, made of 5 mm thick galvanized sheet metal.

Overall weight: 38Kg

Datasheet

Large trash bin Ziggy

Product code G473

Rev. 0 of 01/06/2018



FINISH ACCORDING TO THE CATALOGUE



RAL 9016
(Outer shell and top ring)



RAL 7001
(Sidebands)

Customers can request a different finish from the RAL color options available on our website.

PRODUCT VARIANTS



Product code G473-BIS - Large trash bin with lid Ziggy

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Large trash bin Ziggy

Product code G473

Rev. 0 of 01/06/2018



TREATMENTS AND FINISHES THAT PREVENT CORROSION

Washing

Spray treatment is used to get rid of oils and fats from metal surfaces by using special degreasing liquids. The process involves drying in a dryer for 15 minutes.

Sandblasting

The porosity of metal surfaces is increased by the manual sandblasting process with river sand, which results in an increase in thermosetting powder adhesion.

Anticorrosive application

The first step in the coating process involves using a thermosetting powder anti-corrosion base made of epoxy resins and specific pigments. It provides enough protection against the elements.

Anticorrosive polymerization

The process involves cooking in an industrial curing oven at 180°C. In this step, the powder is transformed into a coating that is uniform, smooth, and lasting.

Polymerization coloured finish

The final phase of coating with thermosetting powders. The application complies with the same principles as the anti-corrosion.

Polymerization colored finish

The final product will be cured in an industrial curing oven at a temperature of 180°C. The procedure is based on the same principles as the polymerization of the anti-corrosion agent. The powder becomes a uniform coating, and the surface becomes the characteristics of the chosen color type, including smooth, peeled, or wrinkled, etc.

3/5

Dimcar si riserva di apportare, in qualsiasi momento, modifiche sui prodotti ritenute utili al miglioramento qualitativo degli stessi; le immagini contenute nelle schede potrebbero non riprodurre fedelmente i colori reali degli articoli.

Datasheet

Large trash bin Ziggy

Product code G473

Rev. 0 of 01/06/2018



DELIVERY

Prodotto fornito in kit di assemblaggio con viteria in acciaio ed istruzioni per il montaggio e fissaggio.

FIXING

Il prodotto è predisposto per il fissaggio al suolo mediante tirafondi e tasselli ad espansione.

CORPORATE CERTIFICATES

ISO 9001:2015

Quality Management System.

UNI EN ISO 3834-3:2021

Welding quality management system.

Processing center

Certificate according to Italian Law D.M. of 17 Jan 2018